Qty:

Date: Jser. □ Thursday, 11/23/2006 11:55:28 AM

Kim Johnston

Process Sheet

Customer

: CU-DAR001 Dart Helicopters Services

Job Number **Estimate Number** : 29668

P.O. Number

: 10820 : HIM

This Issue Prsht Rev. : 11/23/2006

NHA : 28603

S.O. No. : N IM : MACHINED PARTS Type

Part Number

Drawing Name

: D26661

Drawing Number

: D2666 REV. C

Project Number **Drawing Revision** : N/A

Material

Due Date

: 12/5/2006

: SADDLE, INBOARD, LS, 206

12 Um:

Each

Written By

First Issue

Previous Run

Checked & Approved By

Comment

: Est: С

Removed P/O for Powder Coat - in house

processEC

Additional Product

Job Number:



Seq. #:

Machine Or Operation:

Description:

D6101001 1.0



7075-T7351 2X6X6.25



Comment: Qty.:

1.0000 Each(s)/Unit

Total:

12.0000 Each(s)

7075-T7351 2X6X6.25

Issue material from stock: Cut Size 2.0 x 6.25 X 6.0

Grain Along Long 6.0 Length

Batch No: 13 25343

HAAS1



Comment: HAAS CNC VERTICAL MACHIMING #1

Program batch number.

1-Inspect part number and batch number are programmed correctly.

2-Fixturing Inspection last completed on 66,13,16 by

3-Machine Step No 1 of Folio and visually inspect as per attached Dimension Sheet

6-Machine Step No 2 of Folio and visually inspect as per attached Dimension Sheet

8-Machine Step No 3 of Folio and visually inspect as per attached Dimension Sheet

9- Deburr MILLING CONV.

CONVENTIONAL MILLING MACHINE





Comment: CONVENTIONAL MILLING MACHINE

Machine Keyway and inspect per attached dimension sheet

4.0

3.0

QC2

INSPECT PARTS AS THEY COME OFF MACHINE





Comment: INSPECT PARTS AS THEY COME OFF MACHINE



Dart Aerospace Ltd

W/O:		WORK ORDER CH	HANGES					
DATE	STEP	PROCEDURE CHANGE		Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
06.12.14	2	Tool rad of flange pocket should be RO.188. So cresstible holds should be \$6,316, as marked-up on direct Attached DS email	idale-to-	and	06/12/19	12	951642	16.17.G
		-						

Part No: D366-1 PAR #: #IA Fault Category: Pal Machina Parts NCR: Yes No DQA: Date: Octobaz QA: N/C Closed: Date: Octobaz

NCR:		V	VORK OR	DER NON-CONFO	RMANCE (NCR)				
	STEP	Description of NC	Corrective Action		Section B		Verification	Approval	Approval
DATE		Section A	Initial Chief Eng	Action Descript Chief Eng	ion	Sign & Date	Section C	Chief Eng	QC Inspector
06/12/17	2	Tool drive into speldle at the skid how lockstion. Operator error.	Byuz	Drarays and	replace	and 06/12/19	00.12.19	PC 65192	JOS-12-PA
							,		

NOTE: Date & initial all entries

Date: Thursday, 11/23/2006 11:55:29 AM Kim Johnston User: **Process Sheet** Drawing Name: SADDLE, INBOARD, LS, 206 Customer: CU-DAR001 Dart Helicopters Services Part Number: D26661 Job Number: 29668 Job Number: Description: Seq. #: **Machine Or Operation:** SECOND CHECK 5.0 QC8 Comment: SECOND CHECK HAND FINISHING RESOURCE #1 HAND FINISHING1 6.0 Comment: HAND FINISHING RESOURCE #1 Acid etch and Alodine as per QSI 005 4.1 POWDER COATING 7.0 102391 Comment: POWDER COATING (12 Powder Coat White Gloss (Ref: 4.3.5.1) as per QSI 005 4.3 8.0 QC3 Comment: INSPECT POWDER COAT 9.0 PACKAGING 1 Comment: PACKAGING RESOURCE #1 Identify and Stock Location: 5+ 4/83 10.0 Comment: FINAL IN TION/W/O RELEASE Job Completion (Lace 12122

Dart Aerospace Ltd

W/O:		WORK ORDER CHA	NGES				
DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
:							
Part No		PAP # Fault Category	NCD: Vo	No DO	۸.	Data	

QA: N/C Closed: ____ Date: __

NCR:			WORK ORD	ER NON-CONFO	RMANCE (NCR)				
		Description of NC		Corrective Action	Section B		Verification	Annroval	
DATE	STEP	Section A	Initial Chief Eng	Action Descript Chief Eng	ion	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspector
				·					
	·								
				,					

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	29668
Description: 206 Saddle, Inboard, Left side	Part Number:	D2666-1
Inspection Dwg: D2666 Rev. C		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2666 Rev. C and record below:

				Red	corded Acty	ıal Dimensio	ons		
Dim	Min	Max	Go/No Go Gauge	1 /	2 /	3	4 /	Ву	Date
Α	0.100	0.140		./23	. i23	. 123	122		
В	0.100	0.140		.120	.120	. 120	.119		
С	2.470	2.510		2.001	2.501	2.500	2,500		
D	0.100	0.180		.145	.145	145	./ 45		
E	0.210	0.230		2/9	.221	-219	,220,		
F	1.313	1.343		1.323	1.325	1.323	1,328		
G	0.240	0.260		249	.249	.249	,250		
Н	0.615	0.685	<u> </u>	-655	1656	1655	-655		
1	1.125	1.145		1133	1134	1133	1,132	,	
J	0.990	1.010		1.004	1.000	1.000 ,237	- 1 (···
K	0.235	0.240		, 237	,237		.237		
L	0.510	0.515		-512	. SIQ	.512	.512		
М	0.100	0.120		.120	.120	. <i>12</i> 0	./12		
N	1.565	1.585	<u> </u>	1.580	1.581	1,582	1.580		
0	5.990	6.010		6-000	6-002	6.001	6:001		
Р	1.245	1.255		1200	1.250	1.250	1.250		
Q	2.495	2.505		2.500	2.500	2.500	2.500		
R	0.490	0.510		-500	500	.499	.501		
S	0.313	0.318		-319	.314	.314	.314		
T	2.495	2.505		2.497	2.500	2.500	2.499		
U	1.357	1.367		1.362	7.362.	1361	1.362		
V	0.31	0.378		.3/9	-3)8	·31 %	. 318		
W	0.540	0.560		.549	CZZ	.549	.550		
X	1.674	1.684		1.679	1.679	1.678	1.678		
Υ	0.257	0.262		.259	-255	.259	-259		
Z					1				
AA									
AB									
AC									
AD									
AE									
AF						•			

Measured by: SN /スレ	Audited by 🗽 🕞
Date: 06.12.17	Date: 06/12/20

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
С	99.11.10	Added Dim. R-T	RF	
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686 & DT8695 A/B	KJ/RF	
E	06.06.30	Dimension revised per drawing revision C	KJ/JLM	1
F	06.09.19	Reference to DT8888 added to Dim N	KJ/EC	

DART AEROSPACE LTD	Work Order:	29668
Description: 206 Saddle, Inboard, Left side	Part Number:	D2666-1
Inspection Dwg: D2666 Rev. C	·	Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2666 Rev. C and record below:

				Red	corded Actu	ıal Dimensi	ons		
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		/23	-123	0.126	0.116		
В	0.100	0.140		. 119	- 119	0.113	0.113		
С	2.470	2.510		2.501	2.501	2.501	2.501		
D	0.100	0.180		.145	1145	.145	.145		
E	0.210	0.230		-220	. 219	0.216	0.212		
F	1.313	1.343		1.325	1.324	1.318	1.320		
G	0.240	0.260		248		0.251	0.242		
Н	0.615	0.685		.655	.655	.655	-655		
1	1.125	1.145		1.133	1.134	1.128	1.135		
J	0.990	1.010		1.000	1-001	1.002	1.003		
К	0.235	0.240		- 238	238	0.236	0.236		
L	0.510	0.515		.512	-512	0.512	0.572		,
М	0.100	0.120		113	116	0.115	0.40		
N	1.565	1.585	, - <u> </u>	1.580	1.579	1.580	1. 580		
0	5.990	6.010		6-001	6.001	6.001	6.001		
P	1.245	1.255		1.250	1.250	1.250	1,250		
Q	2.495	2.505		2.50U .499	2.500	2.500	2.500		
R	0.490	0.510		.499	.500 .314	0.502	0.502		
S	0.313	0.318		-314	314	,314	.314		
Т	2.495	2.505		2.500	2500	2.500	2.499		
U	1.357	1.367		1.362	7.362	1.361	1.361		<u> </u>
V	0.31	0.328		-318	-318	0.318	0.318		
W	0.540	0.560		. 550	.220	0.550	0.550		
X	1.674	1.684		7.679	1.678	1.678	1.679		
Y	0.257	0.262		-259	,259	.259	-259		
Ζ						,			
AA									
AB									
AC								· .	
AD									
AE									
AF									

		n		
Measured by:	J.L	1 am	Audited by	5
Date:	06/12	118/06/12/19	Date:	36/17/20

Rev	Date	Change	Revised by	Approved
A		New Issue	. RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
С	99.11.10	Added Dim. R-T	RF	
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686 & DT8695 A/B	KJ/RF	
Ē	06.06.30	Dimension revised per drawing revision C	KJ/JLM	_1
F	06.09.19	Reference to DT8888 added to Dim N	KJ/EC	

DART AEROSPACE LTD	Work Order:	29668
Description: 206 Saddle, Inboard, Left side	Part Number:	D2666-1
Inspection Dwg: D2666 Rev. C		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2666 Rev. C and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		0.121	0.119	0.12-1	0.12.1		
В	0.100	0.140		0,114	0.115	0.113	0.116		
С	2.470	2.510		2500	2,499	2.495	2.499		
D	0.100	0.180		0.140	0.140	0,140	0.140		
E	0.210	0.230		0,213	0,213	0.212	0.214		
F	1.313	1.343		1.322	1.322	1,319	1.320		
G	0.240	0.260		0,245	0,243	0,245	0.243		
Н	0.615	0.685		0.655	0.655	0.655	0.655		
	1.125	1.145		1.140	1.138	1.138	1.144		
J	0.990	1.010		1.001	1.001	1.003	1.002		
K	0.235	0.240		0.236	0.236	0,236	0.236		
L	0.510	0.515		0,572	0.572	0,572	0.512		
М	0.100	0.120		01110	0,110	0,110	0.110		
N	1.565	1.585		1.580	1.582	1.580	1.575		
0	5.990	6.010		6.001	6.001	6.001	6.001		
Р	1.245	1.255		1.250	1.250	1.250	1.250		
Q	2.495	2.505		2.500	2.500	2-500	2.500		
R	0.490	0.510		0.502	0.503	0.502	0.502		
S	0.313	0.318		0.314	0.314	0.314	0.314		
Т	2.495	2.505		2,499	2.499	2.500	2.500		
U	1.357	1.367		1.361	1.361	1.361	1.361		
V	0.31	0.378		0.320	0.320	0.320	0.320		
W	0.540	0.560		0.548	0,550	0.548	0.548		
X	1.674	1.684		1.679	1.679	1.679	1.679		
Υ	0.257	0.262		0.258	0.258	0.258	0.258		
Z									
AA									
AB									
AC									
AD									
ΑE					<u></u>				
AF									

_		
Measured by:	Audited by	EB
Date: 06/12/19	Date:	06/12/20

Rev	Date	Change	Revised by	Approved
Α		New Issue	RF	
В	B 99.04.19 Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A		RF	
C	99.11.10	RF		
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686 & DT8695 A/B	KJ/RF	
E	E 06.06.30 Dimension revised per drawing revision C		KJ/JLM KJ/EC	1
F	06.09.19 Reference to DT8888 added to Dim N			
			<i>'</i> (1)	7,01


1959




			The state of the s
DESIG	× 4.	DRAWN BY	DART AEROSPACE USA, INC.
CHECK	KED	APPROVED	DRAWING NO. REV. C
	上	- 	D2666 SHEET 1 OF 1
DATE			TITLE SCALE
 06.0)5.26		SADDLE FWD INSIDE HIGH 1:3
Α		97.03.25	NEW ISSUE
В		97.07.11	ANGLE AND NOTES ADDED
С		06.05.26	INCORPORATE DEO 9122, 9102, 9095

RELEASED a a 14.

UNDER REVIEW



1.808



1.679 1.362 - R0.375 (TYP) 2.500 0.797 0.438 ENGRAVE PART NUMBER AND BATCH NUMBER ø0.257 0 0 0 (TYP 6 PLACES) TO MAX DEPTH
OF 0.010 WITH
MIN RADIUS
OF 0.010 0.922 - RO.50 W16.12.14 \$0,316

1.808

0.550

0.050 X 45° CHAMFER ALL AROUND 0.500 1.250 5HOP COPY RETURN TO

D2666-1 SADDLE FWD INSIDE HIGH

NOTES:

7075-T7351 (QQ-A-250/12) (REF DART SPEC M7075T73B)

MATERIAL:
 FINISH:

ACID ETCH, ALODINE PER DART QSI 005 4.1 POWDER COAT GLOSS WHITE PER DART QSI 005 4.3.5.1

3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

- 4) BREAK ALL SHARP EDGES 0.010 TO 0.020
- 5) D2666-1 SHOWN (D2666-2 IS OPPOSITE)
- 6) ALL DIMENSIONS ARE IN INCHES

ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE

WORK ORDER NO. 29668

Copyright 1997 by DART AEROSPACE USA, INC.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.

Chris Provencal

From: David She

David Shepherd [dshepherd@dartaero.com]

Sent:

October 19, 2006 3:31 PM

To:

'S Shahbazian'

Cc:

'Provencal, Chris'; 'Charbonneau, Eric'

Subject: RE: Radius dimension on the saddle

Change the drawings. I guess we will also change the 0.313 crosstube hole dimensions as well. See D2661 to D2668 as well as D2932 to D2933.

David

From: S Shahbazian [mailto:sshahbazian@dartaero.com]

Sent: Thursday, October 19, 2006 1:16 PM

To: Shepherd, David

Cc: Provencal, Chris; Charbonneau, Eric **Subject:** Radius dimension on the saddle

Dave.

On attach saddle drawing, according to Eric the marked-up radius that reads 0.30 and 0.25, should be 0.188 since the tooling has been changed long time ago, and apparently they have been machining those radiuses to 0.188 for a while. Do you see a problem with that? if not I will go ahead and change the drawing to reflect the changes.

Serge

No virus found in this incoming message.

Checked by AVG Free Edition.

Version: 7.1.408 / Virus Database: 268.13.7/488 - Release Date: 10/19/2006

No virus found in this outgoing message.

Checked by AVG Free Edition.

Version: 7.1.408 / Virus Database: 268.13.7/488 - Release Date: 10/19/2006